

SP-7XL

Full-Rise Scissor Lifts

SKU# 5175994

7,000-lb. Capacity / Scissor Lift / Frame Engaging

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

The Full-Rise Scissor Lift with Collapsible Frames

This space-saving, frame-engaging [scissor lift](#) easily accommodates most passenger vehicles and light trucks and comes complete with pneumatic safety locks, rubber lifting blocks and an open-center for full under-car accessibility. Features a 22" x 63" lift platform, equalization torsion bar, hardened pivot pins, and ergonomic controls.

Features

- 7,000-lb. lifting capacity
- Pneumatic safety locks
- Equalization torsion bar
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile



Specifications

Lifting Capacity	7,000 lbs. (3,175 kg)
Max. Lifting Height	70" (1,781 mm)
Overall Length	165" (4,190 mm)
Overall Width - Min	81.5" (2,072 mm)
Overall Width - Max	87.5" (2,222 mm)
Single Platform Length	62.5" (1,590 mm)
Single Platform Width	22" (554 mm)
Lowered Height	6" (152 mm)
Lifting Time	45 sec
Standard Motor	208-240 VAC / 50-60 Hz / 1 Ph

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.