

# CEMB<sup>®</sup> USA

## SM675

Professional grade articulating swing arm tire changer with leverless mount head and high-performance BPS (Bead Press System) is the perfect choice for all OEM automotive and light truck wheels including difficult to mount stiff side wall low-profile high-performance tires, deep drop center rims and multi-ply commercial and industrial wheel applications. The unique design takes considerably less floor space compared to traditional tilt-back designs and utilizes an extremely rigid column and vertical arm with pneumatic locking and high-quality locking roller guides for long lasting, smooth movement.

[www.cemb-usa.com](http://www.cemb-usa.com)



PROUDLY DISTRIBUTED BY



# SM675



## Leverless Mount Head

Provides simple fingertip activated demounting of high-performance low profile, stiff sidewall run flats and commercial use multi-ply tires.

## Table Top Clamping

Is self-centering with rim diameter index guides to aid in simple external rim clamping avoiding tire and rim scratches.

## High Torque Motor

220v 2-speed motor and heavy-duty transmission handles the most difficult tires and deep drop center rims.



## Bead Press System

Provides simple servicing of stiff sidewall tires and deep drop center rims. Dual bead press aids save time and offers flexibility in multiple mounting method.

## Two Stage Inflation


Utilizes bead sealing jets optimized by placement at the clamping jaws. Pressure limiter provided to ensure operator safety during tire inflation.

## Bead Breaker Shovel

Foot operated side mounted bead breaker shovel combines speed with power for everyday wheel applications to save time.



## DIMENSIONS



|                             |                             |
|-----------------------------|-----------------------------|
| <b>Power Supply:</b>        | 220V, 1ph, NEMA Plug L6-20P |
| <b>Air Pressure:</b>        | 115-145 psi (8-10 bar)      |
| <b>Rim Diameter (Ext.):</b> | 12" - 26"                   |
| <b>Tire Diameter:</b>       | 36" (915 mm)                |
| <b>Max. Wheel Width:</b>    | 15" (380 mm)                |
| <b>Turn Table Speed:</b>    | 8-15 rpm                    |
| <b>Shipping Weight:</b>     | 1050 lbs (476 Kg)           |

## CONTACT

# CEMB<sup>®</sup> USA

CEMB USA - BL Systems Inc.  
2873 Ramsey Road, Gainesville, GA 30501  
(678) 717-1050 - sales@cemb-usa.com  
www.cemb-usa.com