



## MOBILE 2-POST LIFT

MODEL: M-FHB 3500

### A Completely Mobile 2-Post Vehicle Lift

- ◆ Battery operated for total mobility bay to bay or indoors or outdoors
- ◆ A master/slave hydraulic synchronization system that requires no adjustment
- ◆ Automatic locking features make the lift extremely safe
- ◆ Minimal maintenance required; no periodic adjustments
- ◆ No columns to get in the way, allowing unrestricted access to vehicle





Unrestricted access to vehicle because there are no columns to get in the way.



Special adapters allow lifting unique vehicle configurations.



A single person can easily move the lift. An optional fork lift adaptor allows transport over long distances.



Two deep cycle batteries eliminate the need for constant electrical connection.



Optional spot light illuminates the work area under the vehicle.



A 6.4 ft. lifting height allows comfortable access to the vehicle for even the tallest mechanics.

## TECHNICAL DATA

### M-FHB 3500

Lifting Capacity	6,500 lbs
Load Support	4 swivel arms with rubber lift pads - length 22"-51.2"
Lift Pad Height	Min. 4.7"
Lifting Height	6.4'
Drive-in Width	up to 7.5'
Lifting/Lowering Time	Approx. 40 seconds
Drive	Electro-hydraulic
Motor	DC Motor 2.2 KW
Power Source	2 deep-cycle batteries, 24 V, 80 Ah
Connection	Socket 115-230 VAC for battery charger
Load Securing	Hydraulic and Mechanical
Travelling Device	Detachable hydraulic wheel handle, 2 front wheels
Color	Blue RAL5010 , Grey RAL7015

## GLOBAL PLAYER

... in more than 150 countries worldwide

### Subsidiaries

- Australia
- Canada
- Chile
- China
- France
- India
- Ireland
- Japan
- New Zealand
- Poland
- Russia
- Singapore
- Spain
- South Africa
- UK
- USA
- UAE
- Vietnam



**1-866-624-2872**

[www.maha-usa.com](http://www.maha-usa.com)

Follow Us:



**MAHA USA**

2404 E. Hwy 134 | Pinckard, AL 36371 | [sales@maha-usa.com](mailto:sales@maha-usa.com)



**MAHA  
EQUIPMENT  
FINANCE**

More Ways to Help You Buy:  
[www.maha-usa.com/finance.htm](http://www.maha-usa.com/finance.htm)