## TWO POST LIFT





### **SPECIFICATIONS**

Model		ОН-12	OH-12S
Lifting Capacity		12,000lbs (5500kg)	12,000lbs (5500kg)
Lifting Time		69S	69S
Lifting Height	А	72 1/2" ~ 81 1/2" (1842~2071mm)	72 1/2" ~ 81 1/2" (1842~2071mm)
Overall Height	В	174"/186"/198"(4420 / 4725 / 5030mm)	143 1/8"/155 1/8"/167 1/8" (3635 / 3940 / 4245mm)
Overall Width	С	150 3/4" (3829mm)	150 3/4" (3829mm)
Drive-Thru Clearance	D	109 3/4" (2787mm)	109 3/4" (2787mm)
Width Between Columns	Е	123 1/2" (3137mm)	123 1/2" (3137mm)
Minimum Pad Height	F	4 1/2" (115mm)	4 1/2" (115mm)
Motor		2.0HP,220V/60Hz,single phase	
Gross Weight		2,317lbs (1051kg)	2,174lbs (986kg)

## **TWO-POST HEAVY-DUTY LIFTS**

AMGO Heavy-duty two post lifts model OH-12S OH-12 are fitted to any vehicles and garage or commercial shop one lift, three heights, only available in AMGO!







### AMGO HYDRAULIC CORPORATION

SC Division: 1931 Joe Rogers Jr Blvd, Manning, SC 29102, USA Tel:(803)505-6410

TX Division: 4310 Adler, Suite 200, Dallas, TX 75211, USA



## **OH-12 OH-12S**

# 

# TWO-POST HEAVY-DUTY LIFTS

AMGO Two Post Lifts are manufactured on high quality standards by using critical material, advance features and innovated technology.


- √ Single-point safety release;
- √ Overhead safety stop device;
- $\checkmark$  Direct drive cylinder design, without chains and other drive parts;
- ✓ Dual hydraulic direct-drive cylinders, designed and made on high standards;
- $\checkmark$  Self-lubricating UHMW Polyethylene sliders and bronze bushings;
- ✓ Adjustable three height setting accommodate varying service ceiling height.
- √ Automatic arms restraints;
- $\checkmark$  Detachable foot guard and tool tray.



## **FEATURES**



• Single point safety release makes it easier for operators to unlock both columns locks from one column.



• Lifting arms lock automatic release device, high strength gear rack, more stable and reliable.



• The pulley with Self-lubricating bronze bush



• Detachable foot guard and tool tray are equipped as standard

# **TWO POST LIFT**



#### Three-stages Arms

The OH-12 OH-12S with 4 three-stages arms allowing to lift the trucks from short to long wheel base.



#### Standard drop-in adaptors

1.5", 2.5" & 5" extension high adaptors to fit different trucks and lifting height.



#### Saddle adapter (Optional)

Single Screw-up rubber Pad Assembly Kits No.:20803



### Saddle adapter (Optional)

Perfect choice for wide size SUV vehicles light trucks and heavy-duty trucks. Kits No.:20802(suv and light trucks) Kits No.:21103(heavy-duty trucks)

## LESS MAINTENANCE, MORE RELIABLE

OH-12, OH-12S Two post lifts are the new produds developed by AMGO for heavy duty purpose with a lifting capacity up to 12,000lbs. Heavy-duty construction, self-lubricating bush, sliders and high quality parts to make the lifts with almost no maintenance required.

### 5-3-2 warranty:

5 years for steel construction, 3 years for hydraulic parts, and 2 years for electrical components.