






16K 2-POST LIFT

MODEL # CL16-3S & CL16-2-3S / FULL SPECIFICATIONS PG21

This 16,000 lbs. 2-Post Lift boasts optimum flexibility and meets ALI®/ANSI® safety standards. It features **adjustable column extensions to accommodate three settings for height** from either 13' 6" to 14' 6" or add 2' column extensions to go from 15' 6" to 16' 6". **Standard features include 3-stage front and rear arms and low-profile arm supports for a full swing.**

REQUIREMENTS

	13' 6" MINIMUM
	16' RECOMMENDED
	28' RECOMMENDED
	208-230V, 1PH, 30A
	90-120 PSI

12' 10 1/4" 	13' 4 3/4" 	13' 10 1/4" 
--	---	--








20K 2-POST LIFT

MODEL # CL20-0 & CL20-2 / FULL SPECIFICATIONS PG21

Engineered to be wider, taller, and more robust to tackle the heaviest vehicles in your fleet, up to 20,000 lbs. Equipped with 2-Stage arms, this lift also features **adjustable column extensions, adjustable width and the ability to add optional 2' column extensions** for taller vehicles.

REQUIREMENTS

	13' 6" MINIMUM		28' RECOMMENDED
	16' RECOMMENDED		208-230V, 1PH, 30A
	90-120 PSI		

12' 10 1/4" 	13' 4 3/4" 	13' 10 1/4" 
---	--	---

