

R140i SWINGARM SHOP

TOP QUALITY / ENTRY LEVEL PRICE

Heavy duty swing arm structure with exclusive 110v single speed motor provides needed torque and the rigid self-centering chuck with wide clamping range handles a variety of needs. Equipped with galvanized, double-operating bead breaker cylinder.

OPTIONAL UPGRADE PLUS91N HELPER ARM

Air-powered bead top pressing and tire lifting device for large and special tires.



STANDARD PLASTIC TOOL HEAD VSG800A60

Tool head with support for swing arm units.



HAND CONTROLLED SIDE BEAD BREAKER

FEATURES

- Tire Diameters of 40"
- 11" - 22" Outside Clamping
- 13" - 24.5" Inside Clamping
- Table inflation system
- Pressed cast aluminum pedals that can be removed for easy servicing
- Tire paste lubricant and brush

OPTIONAL ACCESSORIES

MOTORCYCLE WHEEL CLAMPS VSG800A99
+ 5" from the outside for 20" - 22" tables



SMALL WHEEL ADAPTER VSG800A111

Reduces clamping capacity to 8" for ATVs and lawn equipment tires. Use with rim clamp tire changers only - requires VSG800A99 wheel clamps.



R140i Series services:



Optional equipment may be required



Site Requirements: 110V / 115-145 psi air supply

Lit# Rotary R140i Changer Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.

TECHNICAL DATA	R140i
External clamping	11" - 22"
Internal clamping	13" - 24.5"
Max. tire diameter	40.5" (1030 mm)
Max. tire width	12" (305 mm)
Max. bead breaker opening	15" (380 mm)
Bead breaker force	6,745 Ft/L lbs (3060 kg)
Rotation speed	7.3 rpm
Max. torque turntable	885 Ft/L lbs (1200 Nm)
Power supply	110v / 10 / 60 Hz