

R146RP SWINGARM PRO

HIGH PERFORMANCE / EXTRA-HEIGHT SPEEDCHANGER

The hand controlled R146RP includes an air-driven PLUS91SA HELPER ARM.* This bead top pressing and tire lifting device for large and special tires features a lower bead lifting roller and pneumatic top bead pressing tool.



Helper arm demounting lower bead

*NOTE: PLUS91SA IS NOT INSTALLED PRIOR TO DELIVERY

FEATURES

- Hand controlled, double-acting bead breaker
- Extra large 46" frame
- 110v drive motor supplies needed torque
- Air tank located in column
- Gear box is supported by steel plates to avoid flex
- Removable pedal assembly for easy maintenance
- Valve tray
- Tire paste lubricant and brush

STANDARD ACCESSORIES



PLASTIC TOOL HEAD

VSG800A60 Tool head with support

VSG800A117 Tool protection kit for metal mount / demount head (2 x kit)

VSG800A6 Clamp Protectors / 24" - 26" (4 pcs)

VSG800A11 Bead breaker protection / Qty. of 1
VSG800A11K / Qty. of 5



Lit# Rotary R146RP Tire Changer Cutsheet.2022.04

©2022 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.

ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.

Site Requirements: 110V / 115-145 psi air supply



OPTIONAL ACCESSORIES

VSG800A107 Fast Fit Motorcycle Adapters
+ 5" from outside

SMALL WHEEL ADAPTER VSG800A11KIT

Reduces clamping capacity to 8" for ATVs and lawn equipment tires.
- requires VSG800A107 wheel clamps

R146R Series services:



Optional equipment may be required

TECHNICAL DATA	R146 Series
External clamping	10" - 26"
Maximum torque to chuck	885 Ft/L bs (1200 Nm)
Internal clamping	12" - 28.5"
Max. tire diameter	45" (1143 mm)
Max. tire width	15" (380 mm)
Max. bead breaker opening	15" (380 mm)
Bead breaker cylinder power at 145 psi	6,745 Ft/L bs (3060 kg)
Power supply	110v / 1Ø / 60 Hz



SCAN CODE FOR PRODUCT VIDEO