## 2 TON ALUMINUM SERVICE JACK

A 49 pound lightweight jack designed for the track side racer or automotive enthusiast that want quick operating performance.

- RapidRise<sup>®</sup> hydraulic power unit with dual pump pistons that raise the lift arm to the load quickly
- Thick frame side plates and reinforced lift arm for added strength, chassis torsion control, and durability
- Angular positioned pump pistons provide maximum effective pump stroke when jack is completely under the vehicle
- Wiper seals protect hydraulic system from contaminants
- Overload and bypass safety valves prevent the jack from being used beyond its rated capacity and prevent ram overextension
- Ball bearing mounted rear swivel caster wheels and wide track front wheels for easy maneuverability
- · Side mounted handles for carrying and easy positioning
- Rubber saddle protector insert prevents scratching and gouging of under car components
- Two piece handle for storage; quick lock feature for engagement and disengagement of handle halves



6602ASJPK - INCLUDES 6602ASJ JACK WITH A PAIR OF 1003AJ JACK STANDS



MODEL#	CAPACITY	LOW HEIGHT	HIGH HEIGHT	CHASSIS	OVERALL	OVERALL	SADDLE DIA.	HANDLE	Shipping
	(TONS)	(IN.)	(IN.)	LENGTH (IN.)	WIDTH (IN.)	Height (In.)	(IN.)	LENGTH (IN.)	Wt. (LBS.)
6602ASJ	2	3.5	19.3	26.5	13	6.5	4.6	50	52.9

## **3 TON ALUMINUM SERVICE JACK**

The market leading big-brother to the 2 Ton 6602ASJ boasting a lightweight aluminum frame and dual pump pistons for rapid rise action.

- RapidRise<sup>®</sup> hydraulic power unit with dual pump pistons that raise the lift arm to the load quickly
- Side mounted handles for easy jack positioning
- Wide track wheels for easy maneuverability
- Rubber saddle pad and foam bumper pad protect vehicle
- Thick frame side plates and reinforced lift arm for added strength, chassis torsion control, and durability
- Wiper seals protect hydraulic system from contaminants
- Overload and bypass safety valves prevent the jack from being used beyond its rated capacity and ram overextension
- Ball bearing mounted rear swivel caster wheels and wide track front wheels for easy maneuverability
- Two piece handle for storage; quick lock feature for engagement and disengagement of handle halves

6603ASJ

6603ASJPK - INCLUDES 6603ASJ JACK WITH 2-PACK OF 1003AJ JACK STANDS



MODEL #	CAPACITY (TONS)	LOW HEIGHT (IN.)	HIGH HEIGHT (IN.)	CHASSIS LENGTH (IN.)	OVERALL WIDTH (IN.)	SADDLE DIA. (IN.)	HANDLE LENGTH (IN.)	SHIPPING WEIGHT (LBS.)
6603ASJ	3	3.8	19.3	26.4	13	4.5	50	58.4