



HEAVY DUTY FLOOR JACKS

A heavy duty service jack designed for continuous, dependable performance in fleet truck shops, farm equipment dealers, bus company garages and commercial vehicle service bays.

- Heavy gauge steel side plates prevent twisting
- Front wheels with roller bearings and ball bearing mounted rear caster wheels provide stability and easy maneuverability
- Rear kick plate helps turn jack in tight places
- Hydraulic power unit is Uniweld constructed for increased strength and leak prevention
- Wiper seals protect hydraulic system from contaminants
- Flash chromed ram and pump piston for rust prevention
- Overload and bypass safety valves prevent the jack from being used beyond its rated capacity and prevent ram overextension
- Foot pump pedal raises the lift arm to the load quickly and "T" handle pumps jack under load
- Lever on "T" handle locks it in any one of three different positions
- Release knob on top of handle operates independently of handle locking lever and any vehicle parked close to the jack

6604 - 5 TON

6606 - 5 TON AIR/HYDRAULIC

6609 - 10 TON

6614 - 10 TON AIR/HYDRAULIC

6620 - 20 TON AIR/HYDRAULIC

MODEL #	CAPACITY (TONS)	LOW HEIGHT (IN.)	HIGH HEIGHT (IN.)	CHASSIS LENGTH (IN.)	OVERALL WIDTH (IN.)	CHASSIS HEIGHT (IN.)	SADDLE DIA. (IN.)	HANDLE LENGTH (IN.)	SHIPPING WT. (LBS.)
6604	5	5	22	55.5	17	9.5	5.75	45.75	225
6606	5 @ 100PSI	5	22	55.5	17	9.5	5.75	45.75	230
6609	10	6.25	22.5	61	18.5	10.5	5.875	45.75	338
6614	10 @ 100PSI	6.25	22.5	61	18.5	10.5	5.875	45.75	364
6620	20	7.3	24.4	67	20.5	11.25	5.7	46	589



10 TON PORTABLE AIR LIFT JACK

Ideal for lifting trucks, trailers, farm and construction equipment, where crowded conditions require single point contact but may be used in pairs.

- 8" diameter pneumatic wheels make maneuverability easy
- Air valve provides speed control when lifting or lowering a load
- T-handle and 8 foot air hose for remote safe positioning and operation
- Extension tubes and detent pins provide multiple lift heights and support after lifting
- Ridged saddle with locating lugs provides excellent gripping surface

6710

MODEL #	CAPACITY (TONS)	LOW HEIGHT (IN.)	RAM TRAVEL (IN.)	MAX. HEIGHT W/ EXT. TUBES (IN.)	OVERALL LENGTH (IN.)	OVERALL WIDTH (IN.)	WHEEL DIA. (IN.)	SADDLE (IN.)	HANDLE LENGTH (IN.)	SHIPPING WT. (LBS.)
6710	10 @ 175 PSI	17.75	11.5	49	58	13.63	8	2 x 5	37.5	176